

# Multifan



Multifan capacities three-phase in m<sup>3</sup>/h (60 Hz)

230/400V 60Hz		0 Pa	30 Pa	50 Pa	80 Pa	100 Pa	150 Pa	250 Pa
n	Type							
1600 rpm	4D30Q	2460	2240	2030	960	730	-	-
	4D35Q	3680	3380	3160	2690	1610	-	-
	4D40Q	5040	4670	4360	3790	3260	-	-
	4D45Q	6440	5940	5560	4860	4230	-	-
	4D50Q	8240	7620	7180	6470	5890	-	-
	4D56 Q	12860	12300	11920	11330	10890	9630	-
	4D63 Q	17470	16870	16460	15820	15360	14000	10430
	4D71 Q	23130	22420	21920	21180	20630	19230	15040
	4D125-4PP-20 1hp Q	34820	29600	25300	-	-	-	-
	4D125-4PP-25 1,5 hp Q	39330	34000	29730	-	-	-	-
1000 rpm	6D50Q	7140	6360	5640	-	-	-	-
	6D56 Q	7620	6780	6090	-	-	-	-
	6D63 Q	12300	11180	10360	8770	5680	-	-
	6D71 Q	15600	14110	13040	11260	9420	-	-
800 rpm	8D71 Q	13300	11630	10270	5420	4200	-	-
	8D92-3PP-21 Q	18930	16120	13870	8310	5380	-	-

All air capacities with wire guard, without casing.

Performance shown is for units without ducts.

Data also valid for tube fans, under same conditions as wall mounting fans.