

# Multifan



Multifan capacities single-phase in m<sup>3</sup>/h (60 Hz)

240V 60Hz		0 Pa	30 Pa	50 Pa	80 Pa	100 Pa	150 Pa	250 Pa
n	Type							
3200 rpm	2E30Q	3610	3460	3340	3110	2930	2270	-
	2E35Q	4520	4310	4180	3920	3730	3400	1740
1600 rpm	4E30Q	2460	2240	2030	960	730	-	-
	4E35Q	3680	3380	3160	2690	1610	-	-
	4E40Q	5040	4670	4360	3790	3260	-	-
	4E45Q	6440	5940	5560	4860	4230	-	-
	4E50Q	8240	7620	7180	6470	5890	-	-
	4E63-3PP-25 Q	10000	8880	8080	6770	5830	-	-
	4E63 Q	17470	16900	16520	15940	15540	14350	12150
1000 rpm	4E125-4PP-20 1hp Q	34820	29600	25300	-	-	-	-
	4E125-4PP-25 1,5 hp Q	39330	34000	29730	-	-	-	-
	4E125-4PP-20 US-version Q	36310	30740	26390	14830	-	-	-
	6E56	10180	9470	8930	7900	7130	-	-
1000 rpm	6E63-3PP-30 Q	9810	8520	7560	5840	3250	-	-
	6E63 Q	12090	11270	10690	9720	8760	-	-
	6E71 Q	12970	12060	11450	10520	9760	6590	-
800 rpm	8E92-3PP-21 Q	18930	16100	14010	9630	5130	-	-

All air capacities with wire guard, without casing.

Performance shown is for units without ducts.

Data also valid for tube fans, under same conditions as wall mounting fans.